

Consumer Products Guide

HIGH TEMPERATURE PAINT



- Silicone formula retains coating film integrity to 1200°F/650°C
- High quality, fast drying formula resists scratching
- Used by many of the leading wood, pellet and gas stove manufacturers as their factory finish
- Easy to apply
- The hearth industry standard for high temperature colors
- Coating holds appearance at high operating temperatures

Mfg. No.	Size	Case Q	ty. Case Wt.
Varies by color	12 oz/340 g spray can	12	14 lbs/ 6.4 kg

Mfg. No.	Color
1990	SATIN BLACK
6159	METALLIC BROWN*
6192	RUSSETT
6193	METALLIC GRAY*
6194	SKY BLUE*
6195	MAHOGANY METALLIC*
6196	METALLIC BLUE*
6197	MOSS GREEN METALLIC*
6198	FOREST GREEN
6199	REDWOOD
6201	CHARCOAL*
6223	EMERALD GREEN METALLIC* ADOBE TAN*
6224	
6230	GOLDENFIRE BROWN* SILVER*
6265	
6283 6298	ALMOND
6302	RICH BROWN METALLIC* METALLIC GOLD*
	FLAT BLACK
6304	HIGH HEAT PRIMER*
6307	SAND
6309	METALLIC BLACK*
6310	BARK BROWN
6311	HONEY GLO BROWN*
6313	MAUVE*
6318	PATRIOT BLUE
6319	MOJAVE RED
6320	COPPER*
6321	PFWTFR*
6324	SUNSET*
6325	SURF SAND*
6327	GREEN ILLUSION*
6329	SHIMMERING ROSE*
6332	NEW BRONZE*
5502	*Metallic
	motanio

INFERNEX® EXTERIOR HIGH TEMPERATURE PAINT



- Silicone formula retains color at high temperatures
- Zinc chemistry fights corrosion for exterior performance
- Easy to apply
- Dries in minutes
- Great coating for fire pits, barbeques, smokers or outdoor fireplace
- Coating holds appearance at high operating temperatures

Item Code	Description
1A251H031	Silver Exterior HT
1A251H050	Metallic Brown Exterior HT
1A251H201	Charcoal HT
1A251H219	Black Exterior HT
1A251H400	Sky Blue Exterior HT

Package	Size	Case Qty	Case Wt.
Aerosol	12oz / 340 g	12	14lbs. / 6.4 kg

BRUSH-ON HIGH TEMPERATURE PAINT





- Silicone formula retains coating film integrity to 1200°F/650°C
- High quality, fast drying
- An alternative to aerosol application
- Brush-on application only
- Coating holds appearance at high operating temperatures

Size	Case Qty.	Case Wt.
Pint	6	8 lbs/ 3.6 kgs
Quart	4	11lbs/ 5 kgs

Ī	Mfg. No.	Color
(62M290	Satin Black
- (62M201	Charcoal
- (62M059	Metallic Brown
(62M830	Goldenfire Brown
(62M209	Metallic Black

GAS VENT PIPE PAINT



- Gloss colors to match major brand porcelain coated gas stoves
- Heat resistant to 250°F/121°C
- Does not require a clear top coat
- This coating is not intended for use on high heat surfaces such as wood stoves, wood stove pipe, pellet stoves or gas stoves.

Mfg. No.	Size	Case Qty.	Case Wt.	
Varies by color	12 oz/ 340 g spray can	6	7 lbs/ 3.2 kgs	



GAS FIRE BOX PAINT

- Special formulation to promote adhesion to aluminized steel
- Resists build-up of white deposits
- Heat resistant to 1200°F/650°C
- Hard finish to resist flame
- Satin Black color

Mfg. No.	Size	Case Qty.	Case Wt.
1A262H227	12 oz/ 340 g spray can	12	14 lbs/ 6.4 kgs



CHIMNEY & ROOF FLASHING PAINT



- Spray flashing to the most popular roofing colors
- Exterior acrylic enamel
- Exceptional durability
- Rapid dry with a matte finish
- Professional finish for any roofing or chimney installation

Mfg. No.	Color
1A464E204	Teak
1A464E206	Charcoal
1A464E305	Terra Cotta
1A464E720	Sea Green
1A464E810	Driftwood
1A464E811	Coffee Brown

Mfg. No.	Size	Case Qty.	Case Wt.
Varies by color	12 oz/ 340 g spray can	6	7 lbs/ 3.2 kgs

BBQ PAINT



- High temperature black paint formulated for outdoor use on BBQ's
- Epoxy additive for animal fat and vegetable oil resistance
- Self priming
- Inhibits rust

Not for use on cooking surfaces

Mfg. No.	Size	Case Qty.	Case Wt.
1A54H204	12 oz/ 340 g spray can	12	14 lbs/ 6.4 kgs

PAINT PREP

- Special formula to clean metal surfaces before painting
- Spray-on wipe-off
- Citrus scent
- Recommended as a surface preparation before applying any Stove Bright[®] paint

Mfg. No.	Size	Case Qty.	Case Wt.
1A80Y010	12 oz/ 340 g spray can	12	14 lbs/ 6.4 kgs



GLASS CLEANER

- Removes creosote on glass doors of wood, pellet & coal stoves
- Non-streaking formula
- Keeps glass doors looking their best
- Pump Spray No propellants

Mfg. No.	Size	Case Qty.	Case Wt.
03M003B16	16 oz/ 473 ml pump spray	12	15 lbs/ 6.8 kgs



GAS APPLIANCE GLASS CLEANER



- Removes white deposits on gas appliance glass surfaces
- Resists future white deposits
- Thick, creamy, no scratch formula

Mfg. No.	Size	Case Qty.	Case Wt.
03M101B4	4 oz/ 118 ml flip top	24	7 lbs/ 3.2 kgs
03M101B8	8 oz/ 237 ml flip top	12	7 lbs/ 3.2 kgs

FIRESTARTER

- Gelled formula stays where you put it
- Lights quick & burns hot
- Colorful visible flame
- For pellet stoves, wood stoves, and campfires

Mfg. No.	Size	Case Qty.	Case Wt.	3
80M400B4	4 oz/ 118 ml flip top	24	7 lbs/ 3.2 kgs	
80M400B8	8 oz/ 237 ml flip top	12	7 lbs/ 3.2 kgs	
80M400B16	16 oz/ 473 ml flip top	12	13 lbs/ 5.9 kgs	7
80M400B32	32 oz/ 946 ml flip top	12	23 lbs/ 104 kgs	
				- 1



THERMOMETER



- Save on fuel consumption
- Longer lasting fires
- Reduce hazardous creosote
- Less chimney cleaning
- Avoid chimney fires
- Attaches magnetically
- Initial firing process instructions included

Mfg. No.	Case Qty.	Case Wt.	
2TSBTHERM	12	1 lbs/ 0.45 kg	

REPLACEMENT GASKETS



Mfg. No.	Size	Length	Case Qty.
	Prepackaged		
2TRGW1408	1/4"	8'	12
2TRGW3808	3/8"	8'	12
2TRGW1208	1/2"	8'	12
2TRGW5808	5/8"	8'	12
2TRGW3408	3/4"	8'	12
2TRGW10008	1"	8'	12
2TRGW11408	1 1/4"	8'	12
E	Black Fiberglass Ro	ре	
2TRGB7808L	7/8" Lopi	8'	12
2TRGB7808CS	7/8" Country Stove	8'	12
Blac	k Tape w/Adhesive	back	NI
2TRCTB780316	7/8 Channel Tape (3/16"channel,1/2" adhesive)	8'	12
2TRMTB180316VC	1/8" x 3/16" (VC)	8'	12
2TRMTB18058	1/8" x 5/8"	8'	12
2TRMTB18034	1/8" x 3/4"	8'	12

GASKET CEMENT

- Formulated for maximum gasket adhesion
- Withstands temperatures over 2000°F/1093°C
- Special cap for easy application
- Special resealable cap for convenient storage and re-use

GASKET CEMENT CEMENT CONTROL OF THE PROPERTY O

Mfg. No.	Size	Case Qty.	Case Wt.
13M200B4Q	4 oz/ 118 ml	12	6 lbs/ 2.7 kgs

RTV SILICONE SEALANT

- Heat resistant
- Special resealable nozzle for convenient storage and re-use

Clear - 500°F/260°C Black - 500°F/260°C Red - 600°F/316°C



Mfg. No.	Size	Case Qty.	Case Wt.
13M050C10SS	10.1 oz/ 298 ml cartridge	12	10 lbs/ 4.5 kgs

M230 SEALANT

- Peak temperature 1100°F/594°C Continuous temperature 900°F/482°C.
- Superior adhesion, integrity and seal when tested to 800°F/427°C for 24 hours against other brands.
- Air dry cures with heat.
- Can be painted with Stove Bright® High Temperature Paint anytime after it air dries (before or after heat cure).
- Does not promote rust when applied to bare metal.
- Special resealable nozzle for convenient storage and re-use.

Mfg. No.	Size	Case Qty	. Case Wt.
13M230C10	10.1 oz/ 300 ml cartridge	12	12 lbs/ 5.4 kgs



DISPLAY RACKS



Standard Floor Display

120 Can Rack with P.O.P. Display Card 58" x 24" x 18" 1473.2 x 609.6 x 457.2 mm

1MJWP000120



Standard Counter Top

24 Can Rack with P.O.P. Display Card 12" D X 17" W 304.8 x 431.8 mm

1MJWP000024



Modified Floor Display

with selection of accessory products and P.O.P. Display 58" x 24" x 18" 1473.2 x 609.6 x 457.2 mm

1MJWP000121

CANS GUNS



- Comfortable trigger spray application
- Easy snap on/snap off feature

1MCANGUN 12/case

Stove Bright® COLOR CARDS

High Temperature Paint Color Cards
Gas Vent Pipe Paint Color Cards
Chimney & Roof Flashing Paint Color Cards



STOVE BRIGHT® Color Fan Decks

High Temperature Paint Color Deck 1MCDSB
Gas Vent Pipe Paint Color Deck 1MCDGVPP



FORREST Technical Coatings